

A

03/05/99

Jc490 U.S. PTO

Please type a plus sign (+) inside this box

→ +

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Approved for use through 09/30/2000 OMB 0651-0032
Patent and Trademark Office U.S. DEPARTMENT OF COMMERCE

PTO/SB/05 (4/98)

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No. 042390.P6054

First Inventor or Application Identifier Mark L. Skarpness

Title METHOD FOR INTERFACING AN ATM NETWORK TO A PC BY

Express Mail Label No. EL236787369US

PTO
09/26/98
Jc490 U.S. PTO

03/05/99

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents

ADDRESS TO: Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

- ☒ Fee Transmittal Form
(Submit an original, and a duplicate for fee processing)
- ☒ Specification [Total Pages 20]
 - Descriptive title of the Invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to Microfiche Appendix
 - Background of the Invention
 - Brief Summary of the Invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
- ☒ Drawing(s) (35 U.S.C. 113) [Total Sheets 6]
- ☒ Oath or Declaration [Total Pages 3]
 - ☒ Newly executed (original copy)
 - ☐ Copy from a prior application (37 C.F.R. § 1.63(d))
(for continuation/divisional with Box 16 completed)
 - ☐ DELETION OF INVENTOR(S)
Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR §§ 1.63(d)(2) and 1.33(b).

- ☐ Microfiche Computer Program (Appendix)
- Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
 - ☐ Computer Readable Copy
 - ☐ Paper Copy (identical to computer copy)
 - ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

- ☒ Assignment Papers (cover sheet & document(s))
- ☐ 37 C.F.R. § 3.73(b) Statement ☐ Power of Attorney
(when there is an assignee)
- ☐ English Translation Document (if applicable)
- ☐ Information Disclosure Statement (IDS)/PTO - 1449 ☐ Copies of IDS Citations
- ☐ Preliminary Amendment
- ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
- ☐ *Small Entity ☐ Statement filed in prior application, Status still proper and desired
- ☐ Certified Copy of Priority Document(s)
(if foreign priority is claimed)
- ☐ Other:

*NOTE FOR ITEMS 1 & 13: IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.27), EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.28).

16. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment.


☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No: _____
Prior application Information: Examiner _____ Group/Art Unit: _____

For CONTINUATION or DIVISIONAL APPS only. The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

17. CORRESPONDENCE ADDRESS

☐ Customer Number of Bar Code Label (Insert Customer No. or Attach bare code label here) or ☒ Correspondence address below

Name	BLAKELY, SOKOLOFF, TAYLOR & ZAFMAN LLP				
Address	12400 Wilshire Boulevard, Seventh Floor				
City	Los Angeles	State	California	Zip Code	90025
Country	U.S.A.	Telephone	(714) 557-3800	Fax	(714) 557-3347

Name (Print/Type)	Kent M. Chen, Reg. No. 39,630		
Signature		Date	03/05/99

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231

Atty. Ref.:042390.P6054
Express Mail No.:

UNITED STATES PATENT APPLICATION

FOR

METHOD FOR INTERFACING AN ATM NETWORK TO A PC
BY IMPLEMENTING THE ATM SEGMENTATION AND
REASSEMBLY FUNCTIONS IN PC SYSTEM SOFTWARE

Inventor(s):

MARK L. SKARPNESS
NIRANJAN PARAMPALLI

Prepared by:

BLAKELY SOKOLOFF TAYLOR & ZAFMAN LLP
12400 Wilshire Boulevard, Seventh Floor
Los Angeles, CA 90025-1026
(714) 557-3800

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to computer systems. More particularly, the invention relates to a method and apparatus for segmenting and reassembling ATM data in an ATM interface.

2. Description of Related Art

Asynchronous transfer mode (ATM) is a connection-oriented cell switching technique in which cells are of a fixed length. Each cell includes a header of 5 bytes and a payload or information of 48 bytes. The header includes virtual channel information and is used in routing. The data portion may carry a variety of information types including voice, data, images, text and video. In recent years, ATM has become universally accepted as the transfer mode of choice for broadband integrated service digital networks (BISDN).

Figure 1 illustrates a typical ATM cell structure of the prior art. ATM cell 100 includes a header 104 and an information field 108. The header is 5 bytes and the information field is 48 bytes to create an ATM cell of 53 bytes. The header is used to identify cells belonging to the same virtual channel and is used

in appropriate routing. Each virtual channel preserves the sequence of the cells.

The header 104 of ATM cell 100 includes six elements including the generic flow control 112, the virtual path identifier 116, the virtual channel identifier 120, the payload type identifier 124 and a header error control 128. The header values are assigned during the connection set up and translated when switched from one section of a network to another section. In particular, the virtual path identifier (VPI) 116 and the virtual channel identifier (VCI) 120 control the routing of the cell.

Typically, in order to prepare and receive ATM data, data must undergo several layers of processing. The lowest layer, a physical layer, performs physical medium dependent functions such as bit timing functions and cell rate decoupling which inserts idle cells in a transmitting direction in order to adapt the rate of the ATM cells to the payload capacity of a transmission system and removes idle cells in the receiving direction. Above the physical layer is an ATM layer which performs header generation and extraction, cell multiplexing and demultiplexing, translation of VPI/VCI fields and generic flow control. An ATM adaptation layer above the ATM layer performs the adaption of the lower layers including the ATM layer and the physical layer to OSI higher layer protocols.

One of those layers, an ATM adaption layer function (AAL functions) is divided into two sublayers, typically, 1) a segmentation and reassembly (SAR) sublayer, and 2) a convergence (CS) sublayer. During transmission, the SAR sublayer performs segmentation of higher layer information into a size suitable for an ATM cell payload. When receiving ATM cells, the SAR sublayer reassembles the contents of the cells of a virtual connection into data units to be delivered to higher layers. The functions of the SAR sublayer are typically performed by hardware implemented in the computer such as a SAR chip. Examples of typical SAR chips are made by Integrated Device Technologies (IDT) of Santa Clara, California, and Motorola Corporation of Schaumburg, Illinois.

Implementing the SAR in a chip has several disadvantages. A first disadvantage of implementing the SAR chip is cost. As the price points of personal computers (PCs) continue to decrease, the additional expense of SAR chips is undesirable. A second disadvantage of using SAR chips is the limited flexibility in changing other components coupled to the SAR chip. Thus, a more inexpensive and flexible method of implementing SAR functions is needed.

[illegible]

In one embodiment of the invention, data to be sent is received.

P6054

BRIEF DESCRIPTION OF THE DRAWINGS

The advantages of the present invention will become more readily apparent to those ordinarily skilled in the art after reviewing the following detailed descriptions and accompanying
5 drawings wherein:

Figure 1 illustrates a typical ATM cell.

Figure 2 illustrates a SAR ASIC coupled to a system as used in the prior art.

Figure 3A and Figure 3B illustrate a system to receive ATM
10 cells which uses software implemented in the CPU to perform the SAR functions.

Figure 4 is a block diagram showing the software SAR module coupled to a simplified ATM interface.

Figure 5 is a flow diagram illustrating processor operations
15 to perform segmentation and traffic shaping functions.

Figure 6 shows transfer of data from various channels to a traffic shaper.

Figure 7 is a flow diagram illustrating operation of a software SAR when receiving data.

DETAILED DESCRIPTION OF THE INVENTION

In the following description, a system and apparatus for providing an interface between a transmitting and receiving unit in a network transferring ATM data will be described. The system
5 uses software implemented in a multipurpose central processing unit to form the segmentation and reassembly functions in a personal computer. The use of software to perform the segmentation and reassembly reduces the cost of building a personal computer. The description which follows will include
10 numerous details set forth in order to provide a thorough understanding of the present invention. For example, details will include bus types and specific examples of processors. However, it will be apparent to one skilled in the art that such specific details are not required in order to practice the present
15 invention.

In order to handle the ATM cells, a prior art SAR chip 208 including an SAR ASIC 212 coupled to a memory buffer 216 is implemented in an overall computer system 220 as illustrated in Figure 2. Computer system 220 receives from a cable 224 such as a
20 fiber or a UTP-5 cable an ATM packet at an ATM physical layer 228. The ATM physical layer 228 performs functions such as bit timing functions, transmission frame adaption to adjust the cell flow according to used payload structure, cell delineation such as scrambling and descrambling to protect the cell delineation

mechanism, HEC sequence generation to correct header errors and cell rate decoupling to adapt the rate of ATM cells to payload capacity. Once completed, the ATM physical layer 228 transfers the processed ATM cells along a bus 232 such as a UTOPIA bus to the SAR chip 208. SAR ASIC 212 performs a reassembly of data for transfer to a bus such as a PCI bus 236. Memory buffer 216 coupled to SAR ASIC 212 stores the completed payload data units (PDU) for transfer to the PCI bus 236.

A PCI bus controller 240 controls the flow of data along PCI bus 236. The PCI bus controller 240 receives interrupts when memory buffer 216 is full. The PDUs may be transferred to a PC memory 244 from PCI bus 236 and subsequently to a CPU 248 for processing.

Figure 3 illustrates an embodiment of the invention in which an ATM physical layer 304 receives data from a cable 308 such as an optical fiber or a UTP-5 cable. The ATM physical layer 304 performs a variety of functions which may include, but is not limited to, bit timing including generation and reception of bit timing information, transmission frame adaption which adapts the cell flow according to the payload structure of the transmission system, cell delineation functions which enable the receiver to recover cell boundaries, header error correction to correct header errors, and cell rate decoupling to remove idle cells during idle periods to adapt the rate of ATM cell transmissions to the payload capacity of the transmission system. A cable such as a UTOPIA bus

308 transfers the output of the ATM physical layer 304 to a PCI bus interface 312. In one embodiment, the PCI bus interface 312 is merely a bridge coupling a PCI bus 316 to a UTOPIA bus 318. The PCI bus 316 is coupled to a host memory 320. A buffer 324, in one embodiment of the invention, a portion of the host memory 320 stores the incoming ATM cells. Typically the ATM cells are concatenated and stored in buffer 324. The size of buffer 324 may vary, a smaller buffer results in more frequency processing of the contents of buffer 324 by a CPU 328 resulting in more interrupts to the CPU. A larger buffer 324 results in fewer interrupts to the CPU 328. However, large buffers result in longer latencies between processing of incoming ATM cells.

The architecture illustrated in Figure 3 allows the connection of other communication devices such as an analog modem 332 to the PCI bus interface 312 using a typical V.90 PCI interface 336 to transport ATM cells across the system bus. The V.90 interface 336 transports input to the PCI bus 316 through PCI bus interface 312. Once the ATM cells are stored in buffer 324, CPU 328 processes the ATM cells to reassemble the data cells during reception and segments the data prior to transmission. By using a CPU 328 which is typically a general purpose microprocessor such as a Pentium II microprocessor from Intel Corporation of Santa Clara, California, significant hardware savings may be had over hardware implementations of a SAR chip.

Figure 3B illustrates a simplified diagram of the flow of information within the computer system. In Figure 3B a UTOPIA bus interface 348 receives ATM cells from a network (not shown). The ATM cells are transferred along an ingress direction 350 to a cell First-In First-Out memory (FIFO) 354 which buffers the data. When the CPU is ready to reassemble the ATM data, the content of FIFO 354 is transferred to PCI bus interface 358 for transfer along route 362 to a CPU which performs reassembly and processing of the ATM data.

When outputting data, the CPU continues to generate new data which is associated with header information to form ATM cells and transferred along route 366 to PCI bus interface 358. The ATM cells are stored in a section of FIFO 354 for eventual transfer along egress route 370 to UTOPIA bus interface 348 for output to the network.

Figure 4 is a block diagram showing the soft SAR module coupled to a simplified ATM interface 404. A reassembly block 408 of the soft SAR receives an incoming stream of ATM cells from one or more ATM virtual circuits (VCs) and reassembles those cells into ATM adaption layer (AAL) protocol data units (PDUs). The AAL protocol PDUs are transferred for output along data path 412 for further processing or for use by the respective processing circuits.

When receiving AAL protocol PDUs, segmentation block 416 receives a stream of AAL protocol PDUs 420 destined for one or more ATM VCs and segments them into ATM cells. A traffic shaping block 424 receives the stream of ATM cells from the segmentation block 416 and outputs a stream of ATM cells for transmission to meet the quality of service (QOS) requirements for each VC and for the entire link.

Figure 5 is a flow diagram illustrating a processor operation to perform the segmentation and traffic shaping functions of segmentation block 416 and traffic shaping block 424 of Figure 4. In block 504 data to be transmitted is supplied in the form of a packet. Each packet may include one or more input buffers. Prior to beginning segmentation, the partial CRC is set to its initial value in block 508. In block 512, the CPU determines whether there are input buffers left in the packet for segmentation into ATM cells. When there is data remaining in the packet, the CPU obtains the next input buffer of data from the packet in block 516.

In block 520, the CPU determines whether the current cell still has remaining space in the information or payload section of the ATM cell. When the information section of a cell is completely full, the CPU writes the cell header for a new ATM cell in block 524. When the information section of the current cell is not full, the CPU continues to copy cell payload data from the input buffer to the information section of the cell in block 528.

In block 532, the CPU computes a new partial cyclic redundancy check (CRC) used to protect against bit errors over the cell payload.

When in decision block 536, the CPU determines that the input
5 buffer is empty, the system goes to decision block 512 to
determine whether there are additional input buffers left in the
packet. In decision block 512, when it is determined that no more
data remains in the packet for transfer to a cell, the system
determines whether the information section of the current cell
10 being processed has at least 8 bytes open in block 540. When the
current cell does not have at least 8 bytes open, the system pads
the remainder of the current cell in block 544 and generates an
additional cell filled with padding except for the last 8 bytes in
block 548. When open space left in the current cell exceeds 8
15 bytes, the open space, except for the last 8 bytes, is filled with
padding data in block 552. After padding the cell in either block
552 or block 548, the final 8 bytes of the cell are filled with
trailer data including, in one embodiment, CPS-UUCPI and AAL5 PDU
length in block 556. The final CRC is also computed and inserted
20 into the final 4 bytes of the trailer in block 560. In block 564
the buffer of ATM cells is delivered for traffic shaping.

A traffic shaper processes the buffer of ATM cells to direct
traffic on a hardware network. Figure 6 illustrates operation of
a traffic shaper 604. Traffic shaper 604 receives a variety of
25 data from a plurality of virtual channels including virtual

channel 1 608, virtual channel 2 612, virtual channel 3 616 up to
virtual channel N 620. Each virtual channel is formed of a
plurality of cell packets such as cell 624, 628, 632 of virtual
channel 608. Traffic shaper 604 receives ATM cells from the
5 buffer of ATM cells and transfers them to a hardware network in a
concatenated order suitable for a receiving device. One example
of a concatenated series of cells is illustrated in output data
stream 636.

In one embodiment of the invention, the soft SAR is also used
10 to receive data from hardware at a processing unit. The procedure
for receiving such data is illustrated in the flow diagram 700 of
Figure 7. In the flow diagram 700 the PCI interface transfers a
plurality of ATM cells to a buffer or "input buffer." The CPU
monitors to determine whether there are cells left in the input
15 buffer in block 708. When there are cells in the input buffer,
the CPU determines whether there is a virtual channel open for the
current cell being processed in block 712. When there is no
virtual channel open for the current cell, the current cell is
dropped in block 716 and the system returns to block 708 to
20 determine when there are cells left in the input buffer in block
708. If there is a virtual channel open for the current cell in
block 712, the CPU copies the cell payload to a reassembly buffer
in block 720. After copying the cell payload to a reassembly
buffer, a new partial CRC over the cell payload is computed in
25 block 724. When the cell received does not have an end of PDU

marker as determined in block 728, the cell is not the last cell in a sequence of data and more data remains to be retrieved so the system returns to block 708 to again retrieve cells from the input buffer.

5 When the cell contains an end of PDU signal in block 728 indicating that the cell is the last cell in a data sequence, the CPU determines whether a CRC matches in block 732. When no CRC match is found an error occurred during data transfer and a portion of a payload data unit (PDU) received so far is dropped in
10 block 734, the system returns to block 708 to determine a number of retrieved cells remaining in the input buffer in block 708. When a CRC match is found in block 732, the CPU determines whether there is a length match in block 736. When the length of the payload data unit does not match the indication for the expected
15 length an error has occurred and the PDU is dropped in block 740. The system returns to determine a number of retrieved cells remaining in the input buffer in block 708.

 When in block 730 the lengths match, the system transfers the PDU to a virtual channel (VC) owner in block 744. In alternate
20 embodiments, the PDU may also be transmitted to an AAL user in block 752. Thus, the software of the system receives the ATM cells and reassembles the data packets transferring only PDUs to the VC owner or to the appropriate AAL user. The process continues until no cells are found in the input buffer of block

CLAIMS

What is claimed is:

1 1. A method of performing asynchronous transfer mode (ATM)
2 segmentation functions comprising the operations of:
3 receiving data to send;
4 segmenting the data to generate a plurality of ATM cells;
5 buffering the plurality of ATM cells in a memory device;
6 traffic shaping the buffered plurality of ATM cells; and
7 transmitting the plurality of ATM cells on a network.

1 2. The method of claim 1 wherein the traffic shaping
2 further comprises:
3 examining a virtual channel and determining whether a cell
4 should be output at a given time; and
5 updating virtual channel information when a cell is to be
6 output at the given time.

1 3. The method of claim 1 wherein the operation of
2 segmenting data is performed by a central processing unit (CPU) of
3 a computer.

1 4. The method of claim 1 wherein the traffic shaping of
2 data is performed by a central processing unit (CPU) of a
3 computer.

1 5. A program storage device readable by a machine, tangibly
2 embodying a program of instructions executable by a machine to
3 perform method steps for segmenting asynchronous transfer mode
4 (ATM) data, the program comprises:

5 a first code section to instruct a CPU of a computer to
6 segment data to generate a plurality of ATM cells;

7 a second code section to buffer the plurality of ATM cells in
8 a memory device; and

9 a third code section to traffic shape the buffered plurality
10 of ATM cells.

1 6. The program storage device of claim 5 wherein the first
2 code section includes instructions to examine a virtual channel
3 and determine whether a cell should be output at a given time and
4 to update virtual channel information when a cell is to be output
5 at the given time.

1 7. The program storage device of claim 5 wherein the
2 program further comprises:

3 a fourth code section to compute a new partial cyclic
4 redundancy check used to protect against bit errors.

1 8. The program storage device of claim 5 wherein the
2 program includes instructions to pad ATM cells which are not
3 complete.

1 9. A method of performing asynchronous transfer mode (ATM)
2 reassembly functions comprising:
3 receiving in an uninterrupted stream a plurality of protocol
4 data units without interrupt in an input buffer, each protocol
5 data unit including a plurality of ATM cells; and
6 retrieving ATM cells from the input buffer until all data
7 corresponding to a payload data unit is retrieved and checking a
8 CRC to determine whether data was received without error.

1 10. The method of claim 9 further comprising:
2 dropping the payload data unit when the CRC indicates an
3 error.

1 11. The method of claim 9 further comprising:
2 copying a cell payload from the input buffer into a
3 reassembly buffer.

1 12. The method of claim 11 further comprising:
2 calculating a new partial CRC corresponding to the cell
3 payload.

1 13. The method of claim 11 further comprising:
2 determining whether the cell payload includes an end of
3 payload data unit marker; and

4 copying a second cell payload from the input buffer into the
5 reassembly buffer when retrieved cell payload does not include the
6 end of payload data unit marker.

1 14. A program storage device readable by a machine tangibly
2 embodying a program of instructions executable by a machine to
3 perform method steps for reassembly ATM data, the program
4 comprising:

5 a first code section to receive a stream including a
6 plurality of protocol data units without interrupt in an input
7 buffer, each protocol data unit including a plurality of ATM
8 cells.

1 15. The program storage device of claim 14 further
2 comprising:

3 a second code section to retrieve ATM cells from the input
4 buffer until all data corresponding to a payload data unit is
5 retrieved and checking a CRC to determine whether data was
6 received without error.

1 16. The program storage device of claim 14 further
2 comprises:

3 a second section to copy a cell payload from the input buffer
4 into a reassembly buffer.

[illegible][illegible]

Fig. 1 (Prior Art)





Fig. 4






Fig. 2 (Prior Art)




Fig. 3A




Fig. 3B




Fig. 5




Fig. 6




Fig. 7

Attorney's Docket No.: 042390.P6054

DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION (FOR INTEL CORPORATION PATENT APPLICATIONS)

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below, next to my name.

I believe I am the original, first, and sole inventor (if only one name is listed below) or an original, first, and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

METHOD FOR INTERFACING AN ATM NETWORK TO A PC BY IMPLEMENTING THE ATM SEGMENTATION AND REASSEMBLY FUNCTIONS IN PC SYSTEM SOFTWARE

the specification of which

☒ is attached hereto.
☐ was filed on _____ as
United States Application Number _____
or PCT International Application Number _____
and was amended on _____
(if applicable)

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claim(s), as amended by any amendment referred to above. I do not know and do not believe that the claimed invention was ever known or used in the United States of America before my invention thereof, or patented or described in any printed publication in any country before my invention thereof or more than one year prior to this application, that the same was not in public use or on sale in the United States of America more than one year prior to this application, and that the invention has not been patented or made the subject of an inventor's certificate issued before the date of this application in any country foreign to the United States of America on an application filed by me or my legal representatives or assigns more than twelve months (for a utility patent application) or six months (for a design patent application) prior to this application.

I acknowledge the duty to disclose all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119(a)-(d), of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s):

APPLICATION NUMBER	COUNTRY (OR INDICATE IF PCT)	DATE OF FILING (day, month, year)	PRIORITY CLAIMED UNDER 37 USC 119
			<input type="checkbox"/> No <input type="checkbox"/> Yes
			<input type="checkbox"/> No <input type="checkbox"/> Yes
			<input type="checkbox"/> No <input type="checkbox"/> Yes

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below:

APPLICATION NUMBER	FILING DATE

Attorney's Docket No.: 042390.P6054

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, Section 112, I acknowledge the duty to disclose all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application:

APPLICATION NUMBER	FILING DATE	STATUS (ISSUED, PENDING, ABANDONED)

I hereby appoint BLAKELY, SOKOLOFF, TAYLOR & ZAFMAN LLP, a firm including: Farzad E. Amini, 42,261; Amy M. Armstrong, P 42,265; Aloysius T. AuYeung, 35,432; W. Thomas Babbitt, 39,591; Carol F. Barry, 41,600; Jordan M. Becker, 39,602; Bradley J. Berezna, 33,474; Michael A. Bernadieu, 35,934; Roger W. Blakely, Jr., 25,831; Gregory D. Caldwell, 39,926; Kent M. Chen, 39,630; Lawrence M. Cho, 39,942; Yongsuck Choi, 43,324; Thomas M. Coester, 39,637; Roland B. Cortes, 39,152; Barbara B. Courtney, P 42,442; Michael A. DeSanctis, 39,957; Daniel M. DeVos, 37,813; Robert A. Diehl, P 40,992; Tarek N. Fahmi, 41,402; James Y. Go, 40,621; Richard L. Gregory, Jr., P 42,607; Dinu Gruia, P 42,996; David R. Halvorson, 33,395; Thomas A. Hassing, 36,159; James A. Henry, 41,064; Phuong Quan Hoang, 41,839; Willmore F. Holbrow III, 41,845; George W. Hoover, 32,992; Eric S. Hyman, 30,139; Dag H. Johansen, 36,172; William W. Kidd, 31,772; Michael J. Mallie, 36,591; Paul A. Mendonsa, P 42,879; Darren J. Milliken, P 42,004; Thinh V. Nguyen, 42,034; Kimberley G. Nobles, 38,255; Michael A. Proksch, P 43,021; Babak Redjaian, 42,096; James H. Salter, 35,668; William W. Schaal, 39,018; James C. Scheller, 31,195; Anand Sethuraman, 43,351; Charles E. Shemwell, 40,171; Maria E. Sobrino, 31,639; Stanley W. Sokoloff, 25,128; Allan T. Sponseller, 38,318; Judith A. Szepesi, 39,393; Vincent P. Tassinari, 42,179; Edwin H. Taylor, 25,129; George G. C. Tseng, 41,355; Lester J. Vincent, 31,460; John P. Ward, 40,216; Stephen Warhola, P 43,237; Charles T. J. Weigell, 43,398; Ben J. Yorks, 33,609; Norman Zafman, 26,250; my attorneys; and Amy M. Armstrong, Reg. No. P42,265; Robert Andrew Diehl, Reg. No. P40,992; and Edwin A. Sloane, Reg. No. 34,728; my patent agents, of BLAKELY, SOKOLOFF, TAYLOR & ZAFMAN, LLP with offices located at 12400 Wilshire Boulevard, 7th Floor, Los Angeles, California 90025, telephone (714) 557-3800, and Joseph R. Bond, Reg. No. 36,458; Richard C. Calderwood, Reg. No. 35,468; Sean Fitzgerald, Reg. No. 32,027; Naomi Obinata, Reg. No. 39,320; Thomas C. Reynolds, Reg. No. 32,488; Steven P. Skabrat, Reg. No. 36,279; Howard A. Skaist, Reg. No. 36,008; Steven C. Stewart, Reg. No. 33,555; Raymond J. Werner, Reg. No. 34,752; and Charles K. Young, Reg. No. 39,435; my patent attorneys, of INTEL CORPORATION with full power of substitution and revocation, to prosecute this application and to transact all business in the Patent and Trademark Office connected herewith.

Send correspondence to Kent M. Chen, Reg. No. 39,630, BLAKELY, SOKOLOFF, TAYLOR & ZAFMAN LLP, 12400 Wilshire Boulevard, 7th Floor, Los Angeles, California 90025 and direct telephone calls to Kent M. Chen, Reg. No. 39,630, (714) 557-3800.
(Name of Attorney or Agent)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Attorney's Docket No.: 042390.P6054Full Name of Sole/First Inventor (given name, family name) Mark L. SharpnessInventor's Signature Mark Sharpness Date 3-4-99Residence Hillsboro, Oregon Citizenship USA
(City, State) (Country)P. O. Address 913 N.E. 3rd AvenueHillsboro, Oregon 97124 USAFull Name of Second/Joint Inventor (given name, family name) Niranjan ParanjapalliInventor's Signature [Signature] Date 3-4-99Residence Santa Clara, California Citizenship India
(City, State) (Country)P. O. Address 618 Robin DriveSanta Clara, California 95050 USA

Full Name of Third/Joint Inventor (given name, family name) _____

Inventor's Signature _____ Date _____

Residence _____ Citizenship _____
(City, State) (Country)

P. O. Address _____

Full Name of Fourth/Joint Inventor (given name, family name) _____

Inventor's Signature _____ Date _____

Residence _____ Citizenship _____
(City, State) (Country)

P. O. Address _____